NSN 5905-00-049-8634

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-049-8634

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.437 inches
Body Diameter:
1.156 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 1.719 inches and 1.781 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.656 inches
Overall Diameter:
2.094 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

A single section

Standard Taper Curve Per Section:

NSN 5905-00-049-8634

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0