Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-049-8641

### Section Quantity:

2

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.688 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.500 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

#### 1.500 inches

Shaft Style:

Round

Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference

### Mounting Method:

Standard bushing

### **Electrical Resistance Per Section:**

6.000 ohms all sections

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

### Power Dissipation Rating Per Section In Watts:

2.5 free air all sections

## **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 all sections

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

### Standard Taper Curve Per Section:

A all sections



Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0