Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-050-1623

## Section Quantity:

2

## Body Style:

Cylindrical servo mounted

### **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

Between 1.5615 inches and 1.5620 inches

#### **Pilot Length:**

0.0600 inches

#### **Overall Length:**

2.375 inches

**Undercut Diameter:** 

Between 1.5615 inches and 1.5620 inches

#### Undercut Width:

### 0.0600 inches

**Body Diameter:** 

1.750 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

#### Body Length:

1.500 inches

#### **Overall Diameter:**

1.750 inches

#### Mounting Lip Diameter:

1.7500 inches

#### Mounting Lip Depth:

0.0600 inches

#### Shaft Style:

Round

## Shaft Bearing Type:

Ball

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

350.0

#### Maximum Starting Torque:

0.30 inch-ounces

#### Maximum Running Torque:

0.30 inch-ounces

# NSN 5905-00-050-1623

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
25.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
175.0 2nd section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.05 to 0.05 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
4.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 2nd section
Tap Location Tolerance Per Section:
-10.0 to 10.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Unpackaged Unit Weight:
7.00 ounces
Terminal Type And Quantity:
8 turret
Shelf Life:

N/a

## NSN 5905-00-050-1623

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0