## NSN 5905-00-050-6787

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-050-6787 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 1.835 inches **Body Diameter:** 0.250 inches **Body Length:** Between 0.325 inches and 0.345 inches **Overall Diameter:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Maximum Starting Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.136 inches and 0.146 inches **Terminal Location:** Rear end **Mounting Method:** Tab **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 290.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.071 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: **Power Dissipation Rating Per Section In Watts:** 

-75.0 to 75.0 single section 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops

## NSN 5905-00-050-6787

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No