Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-050-7037

Section Quantity: 1 **Body Style:** Cylindrical, edge control operated **Reliability Indicator:** Not established **Body Diameter:** 0.720 inches Shaft Diameter: 0.073 inches Shaft Length: 0.145 inches Mounting Stud Length: 0.073 inches **Body Length:** 0.216 inches Shaft Style: Round Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 360.0 **Screw Thread Diameter:** 0.073 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 2 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded stud **Electrical Resistance Per Section:** 1.0 megohms single section **Rotary Actuator Travel In Angular Deg:**

360.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section



Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0