

View Online at <https://aerobasegroup.com/nsn/5905-00-051-4208>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.080 inches

Terminal Length:

0.188 inches

Body Diameter:

Between 1.995 inches and 2.005 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.205 inches

Overall Diameter:

2.188 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

356.0

Maximum Starting Torque:

2.90 inch-ounces

Maximum Running Torque:

1.80 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.004 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.000 ohms 3rd section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.30 to 0.30 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0 to 3.0 2nd section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0