

View Online at <https://aerobasegroup.com/nsn/5905-00-051-7888>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.984 inches

Shaft Diameter:

0.250 inches

Shaft Length:

2.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.062 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

25.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Standard Taper Curve Per Section:

C all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0