Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-052-1794

Section Quantity:

1

Rectangular w/mounting holes Reliability Indicator: Not established Overall Length: 1.050 inches Overall Height:

Body Style:

Between 0.490 inches and 0.510 inches

Overall Width:

Between 0.182 inches and 0.197 inches

Mounting Hole Diameter:

Between 0.090 inches and 0.098 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.050 inches

Body Length:

1.000 inches

Body Width:

Between 0.182 inches and 0.197 inches

Body Height:

Between 0.490 inches and 0.510 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 7200.0 and 16200.0

Maximum Starting Torque:

8.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.513 inches and 0.526 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

NSN 5905-00-052-1794

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 7200.0 and 16200.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-27208/1 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0