Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-052-2284

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Pilot Diameter:

0.96800 inches

Pilot Length:

0.06200 inches

Overall Length:

0.742 inches

Undercut Diameter:

0.975 inches

Undercut Width:

0.05700 inches

Body Diameter:

1.07500 inches

Shaft Diameter:

0.125 inches

0.120 110103

Shaft Length:

0.250 inches

Body Length:

0.680 inches

Mounting Lip Diameter:

1.06200 inches

Mounting Lip Depth:

0.06200 inches

Shaft Style:

Round

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

2.000 kilohms single section

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0