

View Online at <https://aerobasegroup.com/nsn/5905-00-052-6992>

**Section Quantity:**

6

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.9685 inches and 0.9688 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

3.457 inches

**Undercut Diameter:**

1.015 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

Between 0.1244 inches and 0.1249 inches

**Shaft Length:**

Between 0.470 inches and 0.500 inches

**Body Length:**

3.270 inches

**Overall Diameter:**

1.156 inches

**Mounting Lip Diameter:**

1.0620 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

117.0

**Maximum Starting Torque:**

0.72 inch-ounces

**Shaft End Play:**

0.001 inches

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

50.0 ohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Standard Taper Curve Per Section:**

A all sections

**Special Features:**

Second shaft 0.125 in. Maximum lg

**Terminal Type And Quantity:**

18 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0