NSN 5905-00-052-8018

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-052-8018

Section Quantity:

Section Quantity: 1 Body Style: Cylindrical bushing mounted Reliability Indicator: Not established
Body Style: Cylindrical bushing mounted Reliability Indicator:
Cylindrical bushing mounted Reliability Indicator:
Reliability Indicator:
NOT ESTABLISHED
Body Diameter:
0.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.687 inches
Mounting Bushing Length:
0.312 inches
Body Length:
Between 0.980 inches and 1.020 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.290 inches
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:

0.375 inches

NSN 5905-00-052-8018

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0