Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-053-8048

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.030 inches

#### **Terminal Length:**

0.500 inches

**Overall Height:** 

0.500 inches

**Overall Width:** 

0.220 inches

#### Mounting Hole Diameter:

Between 0.075 inches and 0.081 inches

#### Shaft Diameter:

Between 0.077 inches and 0.087 inches

#### Shaft Length:

0.030 inches

## Body Length:

0.500 inches

#### Body Width:

0.220 inches

## **Body Height:**

0.500 inches

## Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Center To Center Distance Between Terminals:

0.200 inches

## Lateral Distance Between Mounting Hole Centers:

0.520 inches

## **Mounting Facility Quantity:**

2

## Terminal Location:

Rear end

## **Mounting Method:**

Unthreaded hole

## **Electrical Resistance Per Section:**

5.0 kilohms single section



Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0