Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-053-8530

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# Reliability Indicator:

Not established

### **Terminal Length:**

0.300 inches

### Mounting Hole Diameter:

0.088 inches

### Shaft Diameter:

0.090 inches

Shaft Length:

### 0.125 inches

Body Length:

### 1.125 inches

**Body Width:** 

0.190 inches

Body Height:

0.320 inches

# Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

7920.0

**Center To Center Distance Between Terminals:** 

0.700 inches

# Lateral Distance Between Mounting Hole Centers:

1.000 inches

# Mounting Facility Quantity:

2

### **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Unthreaded hole

## **Electrical Resistance Per Section:**

200.0 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

7920.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.400 inches



#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## **Actuator Travel Control Feature:**

Clutch

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

### Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 pin

#### Shelf Life:

N/a

#### Unit Of Measure:

--

### Demilitarization:

No

## Fiig:

A002a0