## NSN 5905-00-053-9478

Inductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-053-9478   |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
| -400.0/+400.0   |
| Electrical Resistance:  |
| 6.800 ohms  |
| Resistance Tolerance In Percent:  |
| -5.000 to 5.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 25.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 350.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0 to 350.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Tab, solder lug   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 1.094 inches and 1.344 inches   |
| Body Diameter:  |
| 1.312 inches  |
| Body Length:  |
| Between 10.438 inches and 10.562 inches   |
| Power Dissipation Rating In Watts:  |
| 210.000 free air  |
| Terminal Width:   |
| Between 0.172 inches and 0.328 inches   |
| Cubic Measure (non-core):   |
| 14.195 cubic inches   |
| Unpackaged Unit Weight:   |
| 282.0 grams   |
| Style Designator:   |
| Radial terminal each end  |
| Test Data Document:   |
| 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental           |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Specification Data:   |
| 81349-mil-r-26/3 government specification   |
| Shelf Life:   |

--

N/a

**Unit Of Measure:** 

## NSN 5905-00-053-9478

Inductive Wire Wound Fixed Resistor - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A001a0