NSN 5905-00-054-0478

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-054-0478 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Mounting Hole Diameter:** Between 0.090 inches and 0.096 inches **Shaft Diameter:** Between 0.055 inches and 0.060 inches **Shaft Length:** 0.030 inches **Body Length:** Between 0.492 inches and 0.508 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** Between 0.492 inches and 0.508 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.515 inches and 0.525 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 200.0 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

NSN 5905-00-054-0478

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops and clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**