Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-054-0479

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Mounting Hole Diameter:** Between 0.090 inches and 0.096 inches Shaft Diameter: Between 0.055 inches and 0.060 inches Shaft Length: 0.030 inches **Body Length:** Between 0.492 inches and 0.508 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** Between 0.492 inches and 0.508 inches Shaft Style: Round, slotted Shaft Bearing Type: Bearing Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.515 inches and 0.525 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Cubic Measure:** 0.047 cubic inches **Electrical Resistance Per Section:** 500.0 ohms single section

NSN 5905-00-054-0479

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0