## NSN 5905-00-054-2203

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-054-2203  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -20.0/+20.0  |
| Electrical Resistance:   |
| 215.000 kilohms  |
| Resistance Tolerance In Percent:   |
| -0.500 to 0.500  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 145.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -65.0/+145.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Tab, solder lug  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| Between 0.313 inches and 0.437 inches  |
| Body Diameter:   |
| Between 0.406 inches and 0.594 inches  |
| Body Length:   |
| Between 0.438 inches and 0.562 inches  |
| Power Dissipation Rating In Watts:   |
| 0.250 free air   |
| Err Default:   |
| 0.016 inches   |
| Cubic Measure:   |
| 0.165 cubic inches   |
| Unpackaged Unit Weight:  |
| 1.5 grams  |
| Style Designator:  |
| Radial terminal each end   |
| Test Data Document:  |
| 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental        |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  |
| Specification Data:  |
| 81349-mil-r-93/15 government specification   |
| Shelf Life:  |

--

N/a

**Unit Of Measure:** 

## NSN 5905-00-054-2203

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0