# NSN 5905-00-054-5484

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-054-5484

#### Section Quantity:

1

### Body Style:

Cylindrical bushing mounted

#### **Reliability Indicator:**

Not established

#### **Overall Length:**

2.440 inches

#### First Flat Length:

0.469 inches

#### Flat Height:

0.216 inches

#### Body Diameter:

2.410 inches

#### Shaft Diameter:

0.250 inches

# Shaft Length:

1.000 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

1.440 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

#### **Nonturn Device Location:**

At 12 oclock

#### Nonturn Device Radius:

0.500 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Standard bushing

#### **Electrical Resistance Per Section:**

8.000 kilohms single section

# NSN 5905-00-054-5484

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Power Dissipation Rating Per Section In Watts:** 50.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0