## NSN 5905-00-054-5486

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-054-5486 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.016 inches **Body Diameter:** 1.312 inches **Shaft Diameter:** Between 0.2494 inches and 0.7497 inches **Shaft Length:** 1.125 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.875 inches **Overall Diameter:** 1.374 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:** 0.75 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.562 inches **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

Screw Thready Qty Per Inch (tpi): 32.0

## NSN 5905-00-054-5486

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms single section
Resistance Tolerance Per Section In Percent:
-1.0 to 1.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
250.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-130.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0