## NSN 5905-00-054-6809

Precision Wire Wound Variable Resistor - Page 1 of 3



- redicion time treama tamadie recolcier i age i
View Online at https://aerobasegroup.com/nsn/5905-00-054-6809
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.812 inches
Body Diameter:
1.812 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.712 inches
Mounting Bushing Length:
0.375 inches
Body Length:
2.000 inches
Overall Diameter:
2.156 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Maximum Stop Torque:
550.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.562 inches
Shaft End Play:
0.005 inches

**Shaft Runout:** 0.0005 inches

## NSN 5905-00-054-6809

**Lateral Runout:** 

N/a

Precision Wire Wound Variable Resistor - Page 2 of 3



Lutoral Narioat.
0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25 to 0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug

## NSN 5905-00-054-6809

Precision Wire Wound Variable Resistor - Page 3 of 3



ın	1+	<i>(</i> )+	Measure	•

--

Demilitarization:

No

Fiig:

A002a0