NSN 5905-00-054-7227

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-054-7227

Section Quantity:
1
Body Style:
Rectangular w/tab/flange mounted
Reliability Indicator:
Not established
Thread Length:
0.900 inches
Mounting Hole Diameter:
Between 0.191 inches and 0.211 inches
Shaft Diameter:
0.380 inches
Shaft Length:
1.540 inches
Mounting Stud Length:
1.540 inches
Body Length:
6.110 inches
Body Width:
0.950 inches
Body Height:
1.930 inches
Shaft Style:
Round, threaded
Shaft Bearing Type:
Roller
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Longitudinal Actuator Travel:
Between 3.93 inches and 3.99 inches
Longitudinal Actuator Effective Electrical Stroke Length:
Between 3.930 inches and 3.990 inches
Fragility Factor:
Moderately rugged
Distance Between Mounting Hole Centers:
Between 1.430 inches and 1.450 inches

Between 5.540 inches and 5.560 inches

Lateral Distance Between Mounting Hole Centers:

NSN 5905-00-054-7227

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
Between 0.240 inches and 0.260 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
4
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole and threaded stud
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 kilohms single section
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
350.0 single section
Power Dissipation Rating Per Section In Watts:
9.975 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0