NSN 5905-00-055-1466

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-055-1466 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.250 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 megohms 1st section **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 1st section **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life:

N/a Unit Of Measure:

NSN 5905-00-055-1466

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0