NSN 5905-00-055-3074

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-055-3074 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.500 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Screw Thread Diameter:** 0.112 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 40.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 320.0 **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section

Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
C single section
Special Features:
Case grounded terminal
Terminal Type And Quantity:
2 tab, solder lug

NSN 5905-00-055-3074

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0