## NSN 5905-00-055-3078

**Section Quantity:** 

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-055-3078

Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.750 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.438 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops

## NSN 5905-00-055-3078

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
C single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A002a0