

NSN 5905-00-055-3082 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-055-3082 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 2.500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.781 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.219 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

100.0 ohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Actuator Travel Control Feature:

Continuous motion

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

NSN 5905-00-055-3082

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0