NSN 5905-00-055-3085

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-055-3085 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.912 inches **Shaft Diameter:** 0.248 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.603 inches and 0.671 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 265.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Panel seal **Electrical Resistance Per Section:** 350.0 ohms single section

Rotary Actuator Travel In Angular Deg: 285.0 **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Fixed Tap Quantity Per Section:**

1 single section

NSN 5905-00-055-3085

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
175.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No