Nonprecision Wire Wound Variable Resistor - Page 1 of 2



Nonprecision Wire Wound Variable Resistor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5905-00-055-3100
Section Quantity:
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
0.600 inches
Mounting Stud Length:
0.125 inches
Body Length:
0.625 inches
Actuator Type:
Flush drive with slot-hole
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
40.0
Mounting Facility Quantity:
1
Terminal Location:
Rear end
Mounting Method:
Threaded stud
Electrical Resistance Per Section:
100.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.500 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Mounting stud .075 inch diameter through center of body
Terminal Type And Quantity:
2 tab, solder lug

NSN 5905-00-055-3100

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0