Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-055-3156

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### **Body Diameter:**

1.823 inches

#### Shaft Diameter:

0.248 inches

#### Shaft Length:

0.581 inches

#### Mounting Bushing Length:

0.378 inches

#### Body Length:

#### 1.760 inches

Shaft Style:

Round

### Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

5.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0