

View Online at <https://aerobasegroup.com/nsn/5905-00-055-9343>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.718 inches

**Body Diameter:**

1.000 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.563 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.718 inches

**Overall Diameter:**

1.875 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

321.0

**Maximum Running Torque:**

7.00 inch-ounces

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

300.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

322.0

**Function Conformity Tolerance Per Section:**

-0.50 to 0.50 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0