NSN 5905-00-055-9343

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-055-9343 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.718 inches **Body Diameter:** 1.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.563 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.718 inches **Overall Diameter:** 1.875 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 321.0 **Maximum Running Torque:** 7.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Features Provided: Nonmetallic shaft **Electrical Resistance Per Section:** 300.0 kilohms single section

NSN 5905-00-055-9343

Precision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
322.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0