

View Online at <https://aerobasegroup.com/nsn/5905-00-056-4295>

**Section Quantity:**

11

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.9688 inches

**Pilot Length:**

0.6200 inches

**First Flat Length:**

0.375 inches

**Flat Height:**

0.105 inches

**Undercut Diameter:**

0.968 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

0.1247 inches

**Shaft Length:**

0.437 inches

**Body Length:**

2.680 inches

**Mounting Lip Diameter:**

1.0750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, flatted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

340.0

**Maximum Starting Torque:**

3.45 inch-ounces

**Maximum Running Torque:**

3.45 inch-ounces

**Maximum Stop Torque:**

32.00 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.001 inches

**Pilot Diameter Runout:**

0.001 inches

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

7.5 kilohms 4th section

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

38.17 4th section and 87.27 4th section and 136.37 4th section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-1.50 to 1.50 8th section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

100.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-400.0/+400.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Function Conformity Per Section:**

All sections absolute conformity

**Fixed Tap Quantity Per Section:**

3 4th section

**Tap Location Tolerance Per Section:**

-2.0 to 2.0 degrees angular rotation all sections

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections equation

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 all sections

**Test Data Document:**

97942-577r900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

45 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0