## NSN 5905-00-057-1569

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-057-1569

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.593 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.453 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Radius:
0.245 inches
0.245 inches  Screw Thread Diameter:
Screw Thread Diameter:
Screw Thread Diameter: 0.250 inches
Screw Thread Diameter: 0.250 inches Screw Thread Series Designator:
Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef
Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0
Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location:  Radially positioned over less than half the circumference
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method:
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method: Standard bushing
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section:
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing  Electrical Resistance Per Section: 10.0 kilohms single section
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 10.0 kilohms single section  Power Dissipation Rating Per Section In Watts:
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing  Electrical Resistance Per Section: 10.0 kilohms single section  Power Dissipation Rating Per Section In Watts: 0.5 free air single section
Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing  Electrical Resistance Per Section: 10.0 kilohms single section  Power Dissipation Rating Per Section In Watts: 0.5 free air single section  Resistance Tolerance Per Section In Percent:

3 tab, solder lug

**Terminal Type And Quantity:** 

## NSN 5905-00-057-1569

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0