## NSN 5905-00-057-5242

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-057-5242

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.715 inches
Terminal Length:
0.300 inches
Overall Height:
0.375 inches
Overall Width:
0.203 inches
Shaft Diameter:
0.090 inches
Shaft Length:
0.040 inches
Body Length:
0.375 inches
Body Width:
0.203 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
0.10 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Maximum Stop Torque:
5.00 inch-ounces
Center To Center Distance Retween Terminals:

0.200 inches

## NSN 5905-00-057-5242

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Facility Quantity:
1
Terminal Location:
Front end
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
300.0 to 300.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
20.0 to 20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A002a0