NSN 5905-00-057-8737

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-057-8737

Section Quantity:

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.500 inches Flat Height: Between 0.107 inches and 0.111 inches **Body Diameter:** 0.672 inches **Shaft Diameter:** Between 0.124 inches and 0.126 inches **Shaft Length:** 0.662 inches **Mounting Bushing Length:** 0.188 inches **Body Length:** 0.344 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

NSN 5905-00-057-8737

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Por
--

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

. . . .

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0