NSN 5905-00-058-2476

Fiig: A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-058-2476

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -20.0/+20.0 |
| Electrical Resistance: |
| 12.100 kilohms |
| Resistance Tolerance In Percent: |
| -0.100 to 0.100 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 145.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -65.0/+145.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 1.875 inches and 2.125 inches |
| Body Diameter: |
| Between 0.219 inches and 0.281 inches |
| Body Length: |
| Between 0.688 inches and 0.812 inches |
| Power Dissipation Rating In Watts: |
| 0.250 free air |
| Cubic Measure (non-core): |
| 0.050 cubic inches |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-93/12 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |