NSN 5905-00-058-7452

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-058-7452

Section Overtitus
Section Quantity:
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
0.245 inches
Shaft Length:
0.750 inches
Body Length:
0.453 inches
Shaft Style:
Round, slotted, knurled
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
290.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Flange
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
25.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
290.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-058-7452

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0