NSN 5905-00-058-8934

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-058-8934

•
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
Between 0.515 inches and 0.555 inches
Terminal Length:
0.172 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
0.372 inches
Shaft Diameter:
Between 0.058 inches and 0.098 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.200 inches and 0.270 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7200.0 and 16200.0
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.195 inches and 0.205 inches
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Terminal Location:
Left adjacent side single row
Mounting Method:
Terminal

NSN 5905-00-058-8934

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.095 inches and 0.105 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-27208/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No