Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-058-9173

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Overall Length:**

1.969 inches

#### **Body Diameter:**

1.625 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.530 inches

## Mounting Bushing Length:

Between 0.344 inches and 0.406 inches

**Body Length:** 

1.438 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 6 oclock

#### Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Lower adjacent side single row

# Mounting Method:

Standard bushing

# Features Provided:

Nonmetallic shaft

# **Electrical Resistance Per Section:**

4.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

25.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0