

View Online at https://aerobasegroup.com/nsn/5905-00-059-7421

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-20.0/+20.0

#### **Electrical Resistance:**

26.700 kilohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0 to 145.0

#### **Inclosure Method:**

Encapsulated

#### Terminal Type:

Tab, solder lug

#### **Reliability Indicator:**

Not established

#### **Terminal Length:**

Between 0.313 inches and 0.437 inches

# Body Diameter:

Between 0.468 inches and 0.656 inches

## **Body Length:**

Between 0.938 inches and 1.062 inches

## **Power Dissipation Rating In Watts:**

0.500 free air

## Err Default:

Between 0.141 inches and 0.235 inches

## Cubic Measure:

0.359 cubic inches

## Style Designator:

Radial terminal each end

# Test Data Document:

81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-93/4 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5905-00-059-7421

Noninductive Wire Wound Fixed Resistor - Page 2 of 2

Fiig: A001a0

