NSN 5905-00-059-9871

Fiig: A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-059-9871

Tompurature Coefficient Of Resistance In Ppm Per Deg Celsius: -5.00./+5.0.0 Electrical Resistance: 4.640 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.652 inches Body Length: 0.625 inches Power Dissipation Rating in Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 1349-mil-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 1349-mil-93/3 government specification Shelf Life:	Townwature Coefficient Of Resistance In Daw Box Coleives
Electrical Resistance: 4.640 bms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: -Tab, solder lug Reliability Indicator: Note established Terminal Length: 0.375 inches Body Diameter: 0.652 inches Body Jength: 0.625 inches Power Dissipation Rating in Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 14349-mil-1-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Specification Date: 81349-mil-1939 government specification	
Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Celficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: -0.375 inches Body Diameter: -0.562 inches Body Diameter: -0.562 inches Body Length: -0.625 inches Terminal Width: -0.833 five air Terminal Width: -0.188 inches Style Designator: Radial terminal each end Test Data Document: 1149-mil-1-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 11349-mil-1-93/3 government specification Shelf Life:	
Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.04-145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.376 inches Body Diameter: 0.562 inches Body Diameter: 0.562 inches Power Dissipation Rating in Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-milh-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-milh-93/3 government specification Shelf Life:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: -65.0/+145.0 Inclosure Method: -67.0/+145.0 Inclosure M	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.338 riee air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-milt-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercical catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili-r-93/3 government specification Shelf Life:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab. solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-milr-93/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-93/3 government specification Shelf Life:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Bata Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 1349-mill-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-93/3 government specification Shelf Life:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Diameter: 0.625 inches Body Length: 0.635 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating in Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil93/3 government specification Shelf Life:	145.0
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	-65.0/+145.0
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Inclosure Method:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Encapsulated
Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Terminal Type:
Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Tab, solder lug
Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Reliability Indicator:
Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Not established
Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Terminal Length:
Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	0.375 inches
Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Body Diameter:
Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	0.562 inches
Power Dissipation Rating In Watts: 0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Body Length:
0.333 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	0.625 inches
Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Power Dissipation Rating In Watts:
O.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	0.333 free air
Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Terminal Width:
Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	0.188 inches
Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Style Designator:
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Radial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/3 government specification Shelf Life:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
81349-mil-r-93/3 government specification Shelf Life:	
Shelf Life:	Specification Data:
Shelf Life:	81349-mil-r-93/3 government specification
N/a	
IVa	N/a
Unit Of Measure:	Unit Of Measure:
<u></u>	<u></u>
Demilitarization:	Demilitarization:
No	No