## NSN 5905-00-059-9951

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-059-9951 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.381 inches **Overall Height:** Between 0.292 inches and 0.332 inches **Overall Width:** Between 0.200 inches and 0.240 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.062 inches **Body Length:** 1.319 inches **Body Width:** Between 0.200 inches and 0.240 inches **Body Height:** Between 0.292 inches and 0.332 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 

500.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

9000.0

## NSN 5905-00-059-9951

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
03538-7717791 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure: