NSN 5905-00-060-1941

Section Quantity:

Cylindrical bushing mounted

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-060-1941

Reliability Indicator:
Not established
Overall Length:
1.250 inches
Body Diameter:
Between 1.100 inches and 1.310 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.500 inches
Body Length:
Between 0.578 inches and 0.672 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
117.0
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally closed
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing

NSN 5905-00-060-1941Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:	
Switch	
Electrical Resistance Per Section:	
50.000 kilohms single section	
Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Resistance Tolerance Per Section In Percent:	
10.0 to 10.0 single section	
Switch Current Type And Rating In Amps:	
3.000 ac/dc	
Standard Taper Curve Per Section:	
A single section	
Ferminal Type And Quantity:	
5 tab, solder lug	
Shelf Life:	
N/a	
Jnit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A002a0	