## NSN 5905-00-060-3626

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-060-3626

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| -20.0/+20.0  |
| Electrical Resistance:   |
| 10.000 ohms  |
| Resistance Tolerance In Percent:   |
| -1.000 to 1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 145.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -65.0/+145.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Tab, solder lug  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| Between 0.313 inches and 0.437 inches  |
| Body Diameter:   |
| Between 0.406 inches and 0.594 inches  |
| Body Length:   |
| Between 0.438 inches and 0.562 inches  |
| Power Dissipation Rating In Watts:   |
| 0.250 free air   |
| Terminal Width:  |
| Between 0.141 inches and 0.235 inches  |
| Cubic Measure (non-core):  |
| 0.156 cubic inches   |
| Style Designator:  |
| Radial terminal each end   |
| Test Data Document:  |
| 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental        |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  |
| Specification Data:  |
| 81349-mil-r-93/15 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

No

Demilitarization:

## NSN 5905-00-060-3626

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0