

View Online at https://aerobasegroup.com/nsn/5905-00-060-4522

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-20.0 to 20.0

#### **Electrical Resistance:**

464.000 ohms

**Resistance Tolerance In Percent:** 

-1.000 to 1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0 to 145.0

#### **Inclosure Method:**

Encapsulated

#### Terminal Type:

Tab, solder lug

#### **Reliability Indicator:**

Not established

### **Terminal Length:**

Between 0.313 inches and 0.437 inches

# Body Diameter:

Between 0.468 inches and 0.656 inches

# Body Length:

Between 0.938 inches and 1.062 inches

### **Power Dissipation Rating In Watts:**

0.500 free air

### **Terminal Width:**

Between 0.141 inches and 0.235 inches

### Cubic Measure (non-core):

0.359 cubic inches

### Style Designator:

Radial terminal each end

# Test Data Document:

81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-93/4 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# NSN 5905-00-060-4522

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig: A001a0