## NSN 5905-00-060-5289

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-060-5289

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -25.0/+25.0 second temp coefficient   |
| Electrical Resistance:  |
| 1.620 kilohms   |
| Resistance Tolerance In Percent:  |
| -0.500 to 0.500   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 125.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 145.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0/-25.0   |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Body Diameter:  |
| 0.125 inches  |
| Body Length:  |
| 0.250 inches  |
| Power Dissipation Rating In Watts:  |
| 0.0375 free air   |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,  |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-0  |
| drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any |
| specification, standard or other document that may be referenced in a basic governing drawing)  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |
|   |