NSN 5905-00-060-8499

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-060-8499

Townselves Coefficient Of Bosistans In Bos Bos Don Colsins
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0/+20.0
Electrical Resistance:
32.000 kilohms
Resistance Tolerance In Percent:
-0.500 to 0.500
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0 to 145.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.313 inches and 0.437 inches
Body Diameter:
Between 0.468 inches and 0.656 inches
Body Length:
Between 0.563 inches and 0.687 inches
Power Dissipation Rating In Watts:
0.333 free air
Err Default:
Between 0.141 inches and 0.235 inches
Cubic Measure:
0.154 cubic inches
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-93/3 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 5905-00-060-8499

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0