

View Online at <https://aerobasegroup.com/nsn/5905-00-061-2559>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.828 inches

Body Diameter:

1.656 mils and 1.718 centimeters

Shaft Diameter:

0.250 inches

Shaft Length:

0.878 inches

Mounting Bushing Length:

Between 0.363 inches and 0.393 inches

Body Length:

Between 0.922 inches and 0.984 inches

Overall Diameter:

1.687 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 o'clock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

825.000 ohms c and better flooring

Function Conformity Tolerance Per Section:

-2.00/+2.00 single section

Power Dissipation Rating Per Section In Watts:

4.0 7th secondary quality

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Function Characteristic Per Section:

7 oclock all primaries

Special Test Features:

Navord od36190

Terminal Type And Quantity:

3 tab, solder lug

Reference Number Differentiating Characteristics:

As differentiated by special test features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0