NSN 5905-00-061-2670

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-061-2670

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -50.0 to 50.0 |
| Electrical Resistance: |
| 3.010 ohms |
| Resistance Tolerance In Percent: |
| -1.000 to 1.000 |
| Heat Sink Material: |
| Aluminum alloy |
| Heat Sink Length: |
| 6.000 inches |
| Heat Sink Width: |
| 4.000 inches |
| Heat Sink Height: |
| 2.000 inches |
| Heat Sink Thickness: |
| 0.040 inches |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| |
| -55.0 to 275.0 |
| -55.0 to 275.0 Inclosure Method: |
| |
| Inclosure Method: |
| Inclosure Method: Encased |
| Inclosure Method: Encased Terminal Type: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: Between 0.719 inches and 0.781 inches |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: Between 0.719 inches and 0.781 inches Body Width: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: Between 0.719 inches and 0.781 inches Body Width: Between 0.405 inches and 0.435 inches |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: Between 0.719 inches and 0.781 inches Body Width: Between 0.405 inches and 0.435 inches Body Height: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: Between 0.719 inches and 0.781 inches Body Width: Between 0.405 inches and 0.435 inches Body Height: Between 0.375 inches and 0.405 inches |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: Between 0.719 inches and 0.781 inches Body Width: Between 0.405 inches and 0.435 inches Body Height: Between 0.375 inches and 0.405 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.250 inches and 0.374 inches Body Length: Between 0.719 inches and 0.781 inches Body Width: Between 0.405 inches and 0.435 inches Body Height: Between 0.375 inches and 0.405 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 0.557 inches and 0.567 inches |

Between 0.088 inches and 0.098 inches

NSN 5905-00-061-2670

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Axial terminal (s)

Test Data Document:

81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-18546/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0