NSN 5905-00-061-3922

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-061-3922

O at
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.562 inches
Body Diameter:
Between 1.672 inches and 1.703 inches
Shaft Diameter:
Between 0.234 inches and 0.266 inches
Shaft Length:
Between 0.859 inches and 0.891 inches
Body Length:
Between 1.484 inches and 1.516 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Resistance Tolerance Per Section In Percent:
40.04, 40.0 ; 1, , , ;

A single section

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

NSN 5905-00-061-3922

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



S	рe	cial	Fe	atι	ire	s:
---	----	------	----	-----	-----	----

0.375 in. Long bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0