

View Online at <https://aerobasegroup.com/nsn/5905-00-061-3922>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.562 inches

**Body Diameter:**

Between 1.672 inches and 1.703 inches

**Shaft Diameter:**

Between 0.234 inches and 0.266 inches

**Shaft Length:**

Between 0.859 inches and 0.891 inches

**Body Length:**

Between 1.484 inches and 1.516 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

25.000 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

4.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

0.375 in. Long bushing

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0